

Axitech ES6

Narrow profile with remarkable Class1 output. Universal Multi-Angle Bracket, mounting virtually anywhere.

Operating voltage

12-24V

IP classification

IPX8

Number of LEDs

6 x High-Power LED

Lens color

Clear

Flash patterns

23

Dimensions

130 x 16 X 28mm

Memory function

Yes

Synchronization function

Yes



Color variations

Amber

Product number: 1603-300573
Approvals: ECE R65 (XA1), ECE R10-05 (EMC)
Current: 0.57A @ 12V / 0.29A @ 24V
Current (max): 1.14A @ 12V / 0.57A @ 24V
Power: 13.7W

Blue

Product number: 1603-300574
Approvals: ECE R65 (XB1), ECE R10-05 (EMC)
Current: 0.57A @ 12V / 0.29A @ 24V
Current (max): 1.14A @ 12V / 0.57A @ 24V
Power: 13.7W

Red

Product number: 1603-300612
Approvals: ECE R65 (XR1), ECE R10-05 (EMC)
Current: 0.57A @ 12V / 0.29A @ 24V
Current (max): 1.14A @ 12V / 0.57A @ 24V
Power: 13.7W

White

Product number: 1603-300620
Approvals: ECE R10-05 (EMC)
Current: 0.57A @ 12V / 0.29A @ 24V
Current (max): 1.14A @ 12V / 0.57A @ 24V
Power: 13.7W