

# Axitech ST6

Super thin with superior light output. Amber & Blue colors are available in horizontal and vertical installation that both compliance to the regulation ECE R65 Class 2

**Operating voltage**

12-24V

**IP classification**

IPX7

**Number of LEDs**

6 x High-Power LED

**Lens color**

Clear

**Flash patterns**

29

**Dimensions**

113 x 28 x 9mm

**Operating temperature**

-30 °C - +65 °C

**Memory function**

Yes

**Synchronization function**

Yes



## Color variations

**Amber**

Product number: 1603-300583  
Approvals: ECE R65 (XA2), ECE R10  
Current: 0.60A @ 12V / 0.3A @ 24V  
Current (max): 1.2A @ 12V / 0.6A @ 24V  
Power: 14.4W  
Direction: Horizontal

**Blue**

Product number: 1603-300584  
Approvals: ECE R65 (XB2), ECE R10  
Current: 0.60A @ 12V / 0.3A @ 24V  
Current (max): 1.2A @ 12V / 0.6A @ 24V  
Power: 14.4W  
Direction: Horizontal

**Amber**

Product number: 1603-300593  
Approvals: ECE R65 (XA2), ECE R10  
Current: 0.60A @ 12V / 0.3A @ 24V  
Current (max): 1.2A @ 12V / 0.6A @ 24V  
Power: 14.4W  
Direction: Vertical

**Blue**

Product number: 1603-300594  
Approvals: ECE R65 (XB2), ECE R10  
Current: 0.60A @ 12V / 0.3A @ 24V  
Current (max): 1.2A @ 12V / 0.6A @ 24V  
Power: 14.4W  
Direction: Vertical