

Axitech HB6

6LED Warning Lamp with Halo-Ring 6LED high-performance warning lamp with special outer Halo-Ring™. Independent controlled, multi-purposed outer Halo-Ring as a Clearance Lamp, an Identification Lamp, a Position Lamp, or a Side Marker Lamp.

Operating voltage

12-24V

IP classification

IPX8

Number of LEDs

6 x High-Power LED

Lens color

Clear

Flash patterns

14

Dimensions

132 x 50 x 19mm

Operating temperature

-30 °C - +65 °C

Memory function

Yes

Synchronization function

Yes



Color variations

Amber



Product number: 1603-300597
 Approvals: ECE R65 (XA1) / ECE R91, ECE R10R-05
 Current (max): 1.35 @ 12V / 0.75A @ 24V
 Power: 14.4W

Blue, amber frame



Product number: 1603-300598
 Approvals: ECE R65 (XB1) / ECE R91, ECE R10R-05
 Current (max): 1.35 @ 12V / 0.75A @ 24V
 Power: 14.4W

Blue, silver frame



Product number: 1603-300599
 Approvals: ECE R65 (XB1) / ECE R7, ECE R10R-05
 Current (max): 1.35 @ 12V / 0.75A @ 24V
 Power: 14.4W

Blue



Product number: 1603-300600
 Approvals: ECE R65 (XB1) / ECE R10R-05
 Current (max): 1.35 @ 12V / 0.75A @ 24V
 Power: 14.4W

Blue, red frame



Product number: 1603-300601
 Approvals: ECE R65 (XB1) / ECE R91, ECE R10R-05
 Current (max): 1.35 @ 12V / 0.75A @ 24V
 Power: 14.4W

Amber, red frame



Product number: 1603-300604
 Approvals: ECE R65 (XA1) / ECE R91, ECE R10R-05
 Current (max): 1.35 @ 12V / 0.75A @ 24V
 Power: 14.4W

Amber, silver frame



Product number: 1603-300605
 Approvals: ECE R65 (XA1) / ECE R91, ECE R10R-05
 Current (max): 1.35 @ 12V / 0.75A @ 24V
 Power: 14.4W